SPEED QUEEN MULTI-HOUSING

QUANTUM® GOLD COIN DROP INSTALLED, PREP FOR COIN, PREP FOR CARD

COMMERCIAL TOP LOAD WASHER

Built for Reliable Performance

Speed Queen's two-speed top load washer, defined by its simplicity and its performance, provides everything you need to get the job done – and nothing you don't. Speed Queen's top load washer combines heavy-duty construction with reliable operation proven to stand the test of time. Speed Queen washers provide maximum energy efficiency and long-lasting performance.

- Touch pad control with sound annunciator
- 27 cycle selections
- Extract speed of 710 RPM spins clothes out drier
- Integrated meter case
- Advanced suspension system
- Easy-to-read digital display
- · Cycle programming flexibility
- Multi-level vend pricing
- Individual cycle modifier keys
- Durable stainless steel tub standard
- 3.19 cu. ft. (90.3 liters) wash capacity
- · Large capacity meter case standard
- Wash Alert[™] capability





The cutting edge Quantum control system from Speed Queen gives you the freedom to manage laundry your way with the power to achieve unmatched levels of revenue. Quantum Gold provides users with additional cycle choices while offering new options to help lower operating costs and incorporates tools and options to increase revenue.



SPECIFICATIONS

COMMERCIAL TOP LOAD WASHER

MODEL - see below for all models and activation available		
CONTROL OPTION		Quantum Gold
COLOR		White
CAPACITY - lb (kg)		16 (7.3)
OVERALL WIDTH - in (mm)		25.63 (651)
OVERALL DEPTH - in (mm)		28 (711)
OVERALL HEIGHT - in (mm)		43 (1092)
CYLINDER VOLUME - cu. ft. (liters)		3.19 (90.3)
SPIN SPEED G-FORCE (RPM)		150 (710)
MOTOR SIZE - HP (kw)		0.5 (0.37)
WATER CONSUMPTION PER CYCLE - g	(liter)	28.07 (106)
IWF (WATER FACTOR) - gal/ft³ (liters/liter	/cycle)	8.8 (1.18)
MEF ₁₂ (Modified Energy Factor) ft³/kWh/cycle (Liters/kWh/cycle)		1.35 (38.2)
AVAILABLE WATER TEMPERATURES		Hot, Warm, Cold
AVAILABLE CYCLES		Light, Medium, Heavy, Normal, Perm Press, Delicate
ELECTRICAL REQUIREMENTS (v/Hz/Ph-	-Amp)	120/60/1 - 15 Amp
WATER PRESSURE - p.s.i. (bar)		20-120 (1.4/8.3)
DRAIN		Pump
CYLINDER FINISH		Stainless Steel
NET WEIGHT - lb (kg)		206 (93.4)
SHIPPING WEIGHT - lb (kg)		218 (98.8)
SHIPPING DIMENSIONS APPROX in (mm)	Width	28 (711)
	Depth	30 (762)
	Height	45 (1143)
AGENCY APPROVALS		cULus
·		

•	A	
(
	B	8
	B	<u>&</u>

A.	OVERALL WIDTH - in (mm)	25.625 (651)
B.	OVERALL DEPTH - in (mm)	28 (711)
C.	OVERALL HEIGHT - in (mm)	43 (1092)

MODELS	ACTIVATION
SWNNC2SP115TW02	Coin Drop Installed
SWNNX2SP115TW02 SWNWX2SP115TW02*	Prep for Coin
SWNNY2SP115TW01 SWNWY2SP115TW01*	Prep for Card

^{*}Wireless Network Board Factory Installed

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

